



Sandia
National
Laboratories
SAND2014-17601R



Stability Analysis of HEG Shots 1302 and 1324

Ross Wagnild

Engineering Sciences Center

Sandia National Laboratories

Albuquerque, NM 87123

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000. The views expressed herein are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of Sandia or the U.S. Government.



Stability Analysis Parameters



Sandia
National
Laboratories



- 7° Half-angle circular cone
 - 2.5mm-diameter nose radius, 1.0 m long
 - Grid uses 1215 x 350 cells, axi-symmetric
- Run Conditions - 1302
 - Velocity = 2399 m/s; Density = 10.7 g/m³;
 - Temperature = 264 K; Vibrational Temperature = 264 K
 - Wall Temperature = 293 K; Mach 7.35
 - Mass Fractions
 - N₂ = 0.7527; O₂ = 0.2163; NO = 0.0307; O = 0.0003



Stability Analysis Parameters



Sandia
National
Laboratories



- Run Conditions - 1324
 - Velocity = 4354 m/s; Density = 17.1 g/m³;
 - Temperature = 1286 K; Vibrational Temperature = 1286 K
 - Wall Temperature = 293 K; Mach 6.09
 - Mass Fractions
 - N₂ = 0.7381; O₂ = 0.1601; NO = 0.0619; O = 0.0399
- 5 species air assumed
 - Blended viscosity model based on Sutherland and Blottner data
 - Eucken relation for heat transfer
 - Reacting; Two-temperature non-equilibrium


Maximum N Factor : 1302



Sandia
National
Laboratories



- Max N factor comparison
 - STABL predicts smaller N factor at $s = 1.0 \text{ m}$ (4.9 vs. 5.1)



N factor versus axial distance


Maximum N Factor : 1302



Sandia
National
Laboratories



- Vibrational Temperature
 - Based on experience in the GALCIT T5 tunnel, thermal non-equilibrium exists for enthalpies $< 6\text{MJ/kg}$
 - Estimated thermal non-equilibrium values (+50 K and +100 K) have negligible effect



N factor versus axial distance


Maximum N Factor : 1302



Sandia
National
Laboratories



- Gas Modifications
 - Tested 5 species air compared with perfect gas air
 - Results in negligible difference at this enthalpy
 - Tested a 10% increase in viscosity to increase boundary layer thickness
 - Results in negligible difference



N factor versus axial distance


PSD Comparison: PCB 1



Sandia
National
Laboratories



- Good Agreement
 - STABL predicts a similar most-amplified frequency; a few kHz less than NOLOT
 - STABL predicts a smaller N factor – this requires some further investigation



N factor and PSD versus frequency


PSD Comparison: PCB 1



Sandia
National
Laboratories



- Modifying Vibrational Temperature
 - Small increase has no change (+ 50K , labeled as Vib. Temp = 314 K)
 - Larger increase affects disturbance frequencies (+100 K, labeled as Vib. Temp = 364 K)
 - Based on T5 data – +50 K is feasible, +100 K seems unlikely
 - Nozzle flow simulations with thermal non-equilibrium necessary



N factor and PSD versus frequency


PSD Comparison: PCB 1



Sandia
National
Laboratories



- Perfect Gas in STABL
 - Has a negligible change on most-amplified disturbance frequency
- Modifying Viscosity
 - 10% increase in all species viscosities
 - Nearly matches experimental most-amplified disturbance frequency
 - Labeled Mod. Viscosity



N factor and PSD versus frequency


PSD Comparison: PCB 2



Sandia
National
Laboratories



- Similar Results
 - Comparisons and effects similar for PCB 2



N factor and PSD versus frequency


PSD Comparison: PCB 2



Sandia
National
Laboratories




PCB 2 - 767 mm



N factor and PSD versus frequency

PCB 2 - 767 mm



N factor and PSD versus frequency


PSD Comparison: PCB 3



Sandia
National
Laboratories



- Similar Results
 - Comparisons and effects similar for PCB 3



N factor and PSD versus frequency


PSD Comparison: PCB 3



Sandia
National
Laboratories




PCB 3 - 947 mm



N factor and PSD versus frequency

PCB 3 - 947 mm



N factor and PSD versus frequency


Maximum N Factor : 1324



Sandia
National
Laboratories



- Real Gas Effects
 - ‘Standard’ has 5 species thermochemical non-equilibrium throughout the mean flow and stability analysis
 - ‘Perfect Gas’ has 1 species throughout the analysis
 - ‘Frozen Chem./Vib.’ has 5 species thermochemical non-equilibrium for the mean flow calculation, but not for the stability analysis



N factor versus axial distance



Conclusions



Sandia
National
Laboratories



- Conclusions for Shot 1302
 - Reasonable agreement between NOLOT and STABL
 - Differences in most-amplified disturbance frequency could be due to (among other factors):
 - Thermal non-equilibrium in the mean flow
 - Inaccurate viscosity data
- Conclusions for Shot 1324
 - Current analysis in agreement with previous works:
 - Chemistry and vibration in the mean flow reduce boundary layer stability and increase N Factor
 - Chemistry and vibration have a negligible impact on the disturbance propagation and amplification
 - Comparisons needed for most-amplified disturbances